

# FARMALL® A SERIES TRACTORS

110 – 140 RATED HP

**CASE IH**  
AGRICULTURE



## ONE MULTI-TASKER DESERVES ANOTHER.

You're doing it all – from field to feedlot – but you wouldn't be anywhere else, doing anything else. Case IH understands. That's why Case IH created the Farmall A series. These tractors are tough, reliable, remarkably versatile and an excellent value. The easy-to-use controls allow you to get in and go, and the comfortable operator environment makes a long day seem shorter. Not that you're in any hurry to go inside.





| MODEL        | CYLINDERS | RATED POWER (HP) | ASPIRATION               |
|--------------|-----------|------------------|--------------------------|
| Farmall 110A | 4         | 110              | Turbocharged/Intercooled |
| Farmall 120A | 4         | 118              | Turbocharged/Intercooled |
| Farmall 125A | 6         | 125              | Turbocharged/Intercooled |
| Farmall 125A | 6         | 140              | Turbocharged/Intercooled |

## COMFORT COMES STANDARD.

Hundreds of hours of research go into making long days seem shorter, controls seem more natural and chores seem less challenging in Case IH equipment. Farmall A series tractors continue the long-standing Farmall commitment, putting a high priority on operator comfort and productivity.



**ENJOY THE VIEW.** Choose a Farmall A series ROPS tractor for an outstanding level of visibility and a lower base investment.



### CLIMATE-CONTROLLED COMFORT.

Comfort doesn't have to break the bank. The Farmall A series cab platform keeps the elements out, while delivering the visibility you need to get the job done.



### HAVE A SEAT.

An iso-mounted cab with a large operator platform helps reduce the impact of rough terrain and provide a more comfortable ride. Enjoy the standard contoured seat pictured here or opt for an air suspension seat.

FARMALL A CAB SHOWN

- A** EASY ACCESS TO SIMPLE TO USE CONTROLS
- B** WELL-PLACED, EASY-TO-READ GAUGES
- C** OPTIONAL AIR SUSPENSION SEAT
- D** SPACIOUS OPERATOR PLATFORM
- E** SHOCK AND NOISE-ABSORBING FLOOR MATS



**WORK DAY & NIGHT.**

Ample front and rear lighting is standard on Farmall A series equipment to help you finish up those last few items on your list before the end of the day.

## POWERFUL ECONOMY.

Farmall A tractors are powered by fuel efficient turbocharged, intercooled engines that will work reliably in all conditions. The Farmall A will power efficiently through every task you give it, be it roadside mowing, loading, tilling or haying. These tough, versatile tractors will consistently deliver a flawless performance in the toughest conditions, keeping your costs down.

### ALL THE HORSEPOWER YOU NEED.

The turbocharged FPT engines powering Farmall A tractors (4 cylinder, 4.5 l for the 110A and 120A; 6 cylinder, 6.7 l for the 125A and 140A) are carefully tuned for fuel efficiency and long life. The grid heaters will ensure they start reliably even in the coldest of mornings.



### NON-STOP WORK.

With Farmall A tractors, you won't waste time refuelling. With the large fuel tank (150 litres for 4-cylinder and 235 litres for 6-cylinder models), you can work long days nonstop. And when you do need to refuel, it is a job quickly done, with the easily accessible side-mounted fuel tank under the operator platform.



## TAILOR MADE TRANSMISSIONS.

The transmissions are designed to match the tough, reliable character of Farmall A tractors. Easy and intuitive to use as only Case IH can be, the new, shuttle lever mounted on the column puts control on direction changes at your fingertips while you can comfortably select gear and range with the levers to your right. A high speed 40 kph option or a four-speed creeper option will enable you to tailor your transmission exactly to the job at hand.



### SMOOTH OPERATOR.

Whatever your choice, Farmall A transmissions unfailingly deliver smooth shifting, are easy to use and ergonomically placed. You can go for the standard 8x8 clutchless power shuttle, the 8x8 Synchro mechanical option with mechanical reverser or the optional 16x8 power shuttle with hi-lo gear selection in every range if you really want total control.

## ALL THE POWER YOU NEED.

Farmall A tractors deliver all the hydraulic flow you need to operate even power-hungry implements. The standard dual-pump, open-centre hydraulic system comes with 35 l implement pump. If even this is not enough, you can add a 35 l auxiliary pump to take care of steering and services, so that every ounce of power from the hydraulic system goes to your implement.



### CHAMPION WEIGHTLIFTER.

Productivity soars with the best-in-class hitch lift capacity and all the remote valves you need to change implements easily and quickly. The powerful three-point hitch delivers 23 percent more than competitive tractors in the same class as the Farmall A. The two standard deluxe remote valves with flow control and breakaway couplers can easily be supplemented with two more remotes if needed.

### ALL THE REMOTE VALVES YOU NEED.

Farmall A tractors maximise their excellent versatility with a choice of remote valves. The hydraulic flow to the implement is managed by the two standard closed-centre deluxe rear remote valves with flow control and adjustable detent. You can add four closed-centre, deluxe rear remotes to run multiple hydraulic operations simultaneously. You can control them all comfortably from your seat. Hook-up and operation is intuitive with the colour coded levers that correspond to the color of the remote valves.



## FIT FOR EVERY OPERATION.

You may not actually whistle when you work, but you'll probably smile. That's because the Farmall A series was created to give you everything you need and the option to choose only what you want. And when you're ready for your next Case IH machine, you'll find the resale value will keep that smile right where it is.



### MULTI-TASK LIKE A PRO.

Haying, loading, blading, feeding the cattle and horses. It all needs to be done. Your Case IH dealer will work with you to choose the best options and attachments for your new Farmall A series tractor so you can check tasks off your list quickly and efficiently.



### LOADERS FIT FOR EVERY TASK.

Farmall A tractors can be offered loader-ready, by including an integrated park stand, new joystick and compact, protected bucket level indicator. An increased bucket roll back angle on mechanical self-leveling loaders provides additional leveling capabilities and helps eliminate spillage. A new Multi-Coupler design features flat-faced, no-spill couplers with electrical quick connect. The new Multi-Coupler tool makes it easy to connect all the hydraulics to your loader in one simple operation. It eliminates problems with incorrect connections, pressure in the hoses or oil leaks. The Lock & Go automatic quick coupling system lets you install and remove the loader with minimum effort, no loose parts and no tools.

## MORE THAN TRACTORS TO WORK FOR YOU: WE'VE GOT PEOPLE TO WORK WITH YOU.

When you buy a Case IH machine, you can be sure not only that you're buying the best product, but also that you've got the best dealer back-up behind you. Case IH dealers can offer advice on selecting the right machine, will ensure they deliver what you need when you need it, and will then continue to back you and your equipment with the service and spare parts backing you'd expect from a name as trusted as Case IH.



### SKILLED BUSINESS ADVISOR AT YOUR DEALERSHIP. DEMAND MORE FROM YOUR CASE IH DEALERSHIP.

Purchasing a standalone piece of new equipment?  
Keeping a whole fleet up-to-date? Whatever your size of operation, contact your local Case IH dealership for professional advice on your business needs. Case IH knows your farming needs best.



### MAINTAIN THE PRODUCTIVITY OF YOUR INVESTMENT.

Case IH and its dedicated dealer network provide excellent support when you take delivery of your new machine and whilst it remains in your ownership. On the farm, you can rely on trained service professionals to maintain the productivity of your investment.



### DO NOT RISK YOUR MACHINE'S LIFE. BUY CNH INDUSTRIAL PARTS & SERVICE!

Protect the value of your investment. Behind every Case IH product stands an extensive parts logistics organisation, stocking parts for products both old and new. Choosing to fit genuine Case IH parts will maintain the safety, value and performance of your original investment.

# FARMALL A SERIES SERIES TRACTORS SPECIFICATIONS

Since 1923, the Farmall name has been synonymous with power, performance, durability and value. Case IH is proud to expand the Farmall A heritage with a new line of 110–140 HP tractors. These workhorse tractors provide value without compromise with many no-nonsense standard features, as-well-as factory options and dealer-installed options to create a tractor right for your operation at the right price.

| FARMALL A SPECIFICATIONS                                  | FARMALL 110A                                                        | FARMALL 120A  | FARMALL 125A        | FARMALL 140A   |
|-----------------------------------------------------------|---------------------------------------------------------------------|---------------|---------------------|----------------|
| POWER                                                     |                                                                     |               |                     |                |
| Type                                                      | Tier 3                                                              |               |                     |                |
| Engine HP at 2,200 RPM                                    | 110                                                                 | 118           | 125                 | 140            |
| PTO HP at 1,900 RPM                                       | 95                                                                  | 98            | 105                 | 117            |
| Number of Valves                                          | 8                                                                   |               | 12                  |                |
| Aspiration                                                | Turbocharged                                                        |               |                     |                |
| ELECTRICAL                                                |                                                                     |               |                     |                |
| Alternator Standard                                       | 120 Amp                                                             |               |                     |                |
| Battery Standard                                          | 12V-950 CCA                                                         |               |                     |                |
| TRANSMISSION/PTO                                          |                                                                     |               |                     |                |
| Standard (Base)                                           | 8x8 synchronized mechanical shuttle w/ left hand shuttle            |               |                     |                |
| Optional                                                  | 8x8 synchronized hydraulic shuttle w/ left hand shuttle             |               |                     |                |
| Optional                                                  | 16x8 dual power synchronized hydraulic shuttle w/ left hand shuttle |               |                     |                |
| Creeper option                                            | Available for all transmission                                      |               |                     |                |
| PTO - Standard/Optional (with Two Individual Shafts)      | 540 / 540 - 1,000                                                   |               | 540 - 1,000 / -     |                |
| AXLES                                                     |                                                                     |               |                     |                |
| Standard/Rear Axle                                        | Flange / Bar                                                        |               |                     |                |
| Bar Axle Diameter                                         | 78 mm                                                               |               |                     |                |
| Rear Bar Axle Length                                      | 2 489 mm                                                            |               |                     |                |
| Front Axle - Standard /Optional                           | 2WD / Class 3 Non-Suspended Standard-Duty                           |               |                     |                |
| Tread Adjustability                                       | 1,626 – 2,032 mm                                                    |               |                     |                |
| Wheelbase Standard 2WD/MFD                                | 2,570 mm / 2,520 mm                                                 |               | 2,667 mm / 2,642 mm |                |
| HYDRAULICS/HITCH                                          |                                                                     |               |                     |                |
| System Type Standard                                      | Fixed Displacement Pump (FD)                                        |               |                     |                |
| Remotes - Standard /Optional                              | 1 Deluxe Remotes / 4 Deluxe Remotes                                 |               |                     |                |
| Implement Flow Capacity - Standard/Optional               | 49/84 L/min                                                         |               |                     |                |
| Steering/Secondary Pump Capacity                          | 30 L/min                                                            |               |                     |                |
| Tractor Hydraulic Total Flow Capacity - Standard/Optional | 83/132 L/min                                                        |               |                     |                |
| 3-Point Hitch Category                                    | Cat II standard                                                     |               |                     |                |
| Lift capacity (OECD@610mm) standard / option 1 / option2  | 2,410 kg / 3,639 kg / 4,647kg                                       |               |                     |                |
| CAPACITIES                                                |                                                                     |               |                     |                |
| Fuel Tank                                                 | 150 l                                                               |               | 235 l               |                |
| Engine Oil with Filter                                    | 11 l                                                                |               | 14 l                |                |
| Hydraulic Fluid                                           | 62 l                                                                |               |                     |                |
| CAB                                                       |                                                                     |               |                     |                |
| Mounting                                                  | Iso-Mounted                                                         |               |                     |                |
| Seat - Standard/Optional                                  | Mechanical / Air suspension                                         |               |                     |                |
| WEIGHT                                                    |                                                                     |               |                     |                |
| 2WD w / ROPS, lbs. (kgs)                                  | 8,003 (3,630)                                                       | 8,091 (3,670) | 9,061 (4,110)       | 9,061 (4,110)  |
| MFD w / ROPS, lbs. (kgs)                                  | 8,642 (3,920)                                                       | 8,818 (4,000) | 9,700 (4,400)       | 9,700 (4,400)  |
| 2WD w / cab, lbs. (kgs)                                   | 8,708 (3,950)                                                       | 8,885 (4,030) | 9,766 (4,430)       | 9,766 (4,430)  |
| MFD w / cab, lbs. (kgs)                                   | 9,348 (4,240)                                                       | 9,524 (4,320) | 10,406 (4,720)      | 10,406 (4,720) |

<sup>†</sup>FPT Industrial-engine <sup>1)</sup>ECE R-120 correspond to ISO TR14396



 Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment. Case IH recommends **ARCELA** lubricants.

Case IH EMEA Brand Communications - Steyrer Strasse 32, 4300, Sankt Valentin, Austria - © 2014 CASE IH - Visit our website: [www.caseih.com](http://www.caseih.com)  
Send us an e-mail: [Africa.MaxService@caseih.com](mailto:Africa.MaxService@caseih.com) - [MiddleEast.MaxService@caseih.com](mailto:MiddleEast.MaxService@caseih.com) - Farmall\_A\_Series\_English - Cod. N. 14MEAC0008